

# **GT SERIES**ROBOTIC TOTAL STATION





# The Ultimate Total Station

- UltraSonic Direct Drive motors
- 30% smaller and lighter than any previous Topcon robotic
- TSshield™ global service
- Advanced UltraTrac technology
- 3-year instrument warranty
- 5-year motor warranty
- Available in two models

The GT Series of robotic total stations is a compact, high-performance solution. You get the efficiency of a single-operator robotic system, the power of long-range reflectorless measurements, and performance as a hybrid positioning solution.

#### Ultra-powerful

UltraSonic technology is the driving force for the GT Series. The UltraSonic motors are the thinnest, lightest, and most powerful on the market – providing you with the smoothest and most accurate prism-tracking possible. It's a difference you can see and hear immediately.

#### Ultra-accurate

Our new UltraTrac technology gives you increased prism-tracking strength in all conditions. Advanced instrument algorithms deliver the confidence you need to move ahead. It's not that you lose line-of-sight, it's how fast you can reacquire and get back to work.

#### Ultra-slim and reliable

Featuring a remarkably slimmed down design, the compact system is a third smaller and lighter than any Topcon robotic instrument, yet twice as fast. Without traditional gears or wearing parts, the UltraSonic motors are more rugged and durable – lasting four times longer than previous total stations, and we back it with a five-year warranty.



# Workdays turned into workflows


- Direct connectivity to both MAGNET® Enterprise and Sitelink3D global web services
- Easy collaboration from project sites to office staff and managers
- Instant file sharing with both Autodesk® AutoCAD
  Civil 3D and Bentley MicroStation

# UltraSonic Motor

Experience power like you've never seen or heard before

- Long-lasting gearless design
- Turning speed of 180° per second
- Compact motor efficiency

fastest robotic motor technology available





Telescope	
Resolving power	2.5"
Magnification	30x
Angle Measuremer	nt
GT-502: 2"	GT-1001: 1"
GT-503: 3"	GT-1002: 2"
GT-505: 5"	GT-1003: 3"
Tilt Angle Compensation	
Compensation	Liquid 2-axis tilt sensor
Range	±6'
Distance Measurement	
Prism EDM Range	
GT-500	4,500 m
GT-1000 Prism EDM Accuracy	5,000 m
GT-500	2 mm + 2 ppm
GT-1000	1 mm + 2 ppm
Non-Prism Range	
GT-500	800 m
GT-1000	1,000 m
Non-Prism Accuracy	2 mm + 2 ppm (0.3 - 200 m)
Measuring Time	Fine: 0.9 sec
	Rapid: 0.6 sec Tracking: 0.4 sec
Communications	racking. 0.4 300
LongLink™ interference	e-free communication
USB 2.0 Slot (Host + Slave)	
RS-232C Serial	
General	
Display	Color touch TFT
	800 x 480 display
Keyboard	24 keys with illuminator
Battery Operation	Up to 4 hours
Dust/Water Rating	IP65







- Instant Internet connection from project site
- MAGNET® Field on-board for team collaboration
- Asset management through MAGNET® Enterprise service

# Sharp display

- Larger and brighter color touch screen
- User-friendly interface with simple setup routines and hot keys
- Faster processor for improved response time



#### Versatile solution

- Hybrid Positioning<sup>™</sup> with quick addition of compatible Topcon GNSS receiver
- Compatible with RC-5 remote
- Reflectorless out to 1,000 m



### Guaranteed reliability

- 3-year instrument warranty
- 5-year UltraSonic motor warranty
- TSshield<sup>™</sup> for worry-free theft deterrence and firmware maintenance



Wireless Connection Bluetooth® Class 1

-20°C to 50°C

120° per-second

180° per-second

Operating Temp

Turning Speed

GT-500

GT-1000

For more information: topconpositioning.com/gt-series

Specifications subject to change without notice. ©2016 Topcon Corporation All rights reserved. T630EN B 6/16

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.